



HTM-750 **Heat Transfer Cement**



Description

HTM-750 heat transfer cement is designed to significantly improve the heat transfer between tracers and process lines. Heat transfer cement thermally bonds steam and electric heat tracers to process pipes, valves, pumps and other equipment. HTM-750 fills the air cavities that normally exist between the heat tracer and process equipment with heat conductive, thermal mastic that efficiently transfers heat through conduction to the process equipment. By replacing the normal air gaps with the heat conductive cement, the heat transfer rates are improved by up to 10 times that of convective heat transfer.

Ratings

Maximum Exposure Temperature: **750°F**
Minimum Application Temperature: **32°F**
Heat Transfer Coefficient: **20-40 BTU/Hr-Ft²°F**

Soluble in Water
Shelf Life: **1 Year Unopened**

AEF MANUFACTURING
210 DEERSLAYER DR.
SEGUIN, TX 78155

Phone: 830.401-0520
Fax: 830.401-0520
Email: sales@aefmfg.com




HTM-750 Heat Transfer Cement

Features

- Thermally bonds steam, fluid, and electric heat tracers to process pipes, vessels and equipment.
- With its high conductivity, significantly improves heat transfer between steam and fluid tracer tubes and process pipes; also plate-type steam, fluid and electric heating coils installed on storage and processing tanks.
- Provides an easy to install, cost effective alternative to jacketed piping and internal tracer systems.
- One tracer installed with HTM-750 will deliver the equivalent heat of up to four bare (no HTM) tracers. With the elimination of multiple tracers, the costs to install and maintain the tracing system is greatly reduced.



Optional HTM Channel reduces waste, weather protects and eliminates curing requirements



Ordering Information

HTM-750-1	One Gallon Container	15 Lbs
HTM-750-5	Five Gallon Container	75 Lbs
HTM-750-Q	Quart Size Container	4 Lbs
HTM-750-C	0.10 Gallon Cartridge	1.5 Lbs

Accessories

HTM#2	Metal Channel For 1/4" Tracer(4' Length)
HTM#4	Metal Channel For 1/2" Tracer(4' Length)
HTM#7	Metal Channel For 3/4" Tracer(4' Length)
HTM-SSB	Stainless Steel Banding (100 Ft.)
HTM-SSCR-1	S.S. Crimp Seals for Banding (ea)



Typical hand trowel application

Note: Material Safety Data Sheet (MSDS) available.

AEF MANUFACTURING
210 DEERSLAYER DR.
SEGUIN, TX 78155

Phone: 830.401-0520
Fax: 830.401-0520
Email: sales@aefmfg.com